

W2-LFS-630 WIRELESS LOW FREQUENCY SOUNDER



- Compatible with any **Wi-Safe 2** product.
- Mains powered with rechargeable battery back-up.
- Provides additional protection by sounding loud blasts at a low frequency signal. It is likely to wake up high risk individuals including children, those with mild to moderate hearing loss, older people and people under the influence of alcohol than a regular smoke alarm.
- Emits a 520HZ square wave at a volume of 85dB(A) at 3m and the red 'alarm' LED will also illuminate.
- Will activate if smoke or CO triggers any alarm in the network.
- Will detect and indicate a low battery warning with any smoke, heat or CO alarm within the network.
- Can be wall mounted or free-standing, offering flexibility in positioning.
- Enables low level testing of all interlinked products in the network, avoiding the need to reach up to ceiling mounted alarms to test.



Technical Specification

Dimensions	198mm (width) x 108mm (height) x 57.8mm (depth)	
Supply voltage	230V AC, 50Hz	
Battery back-up	Rechargeable 5 year NI-MH battery	
Technology	Wi-Safe 2	
Alarm sound level	85dB(A) at 3m (minimum)	
Installation positions	Free-standing or wall mounted vertically or horizontally	
Operating temperature	+4°C to +38°C	
Operating humidity	Up to 90% RH non-condensing	
Storage temperature	-20°C to 60°C	
Storage humidity	Up to 93% RH non condensing	
Plastic material	ABS, UL94 VO fire retardant	
Warranty	5 years	
Weight	635g	
Certified to	N/A	
Independently tested to	EN 300 220-2 V 2.4.1 EN 301 489-3 V 1.6.1 EN 301 489-1 V 1.9.2	
Maximum number of connected units	50 wireless units	
Operating Frequency	868 MHz	
Range	35m (over 200m in clear air)	

For further information or sales enquires: www.fireangel.eu

GN4628R1