

WG-1T WI-SAFE GATEWAY

Wi-Safe[®] CONNECT

Enabling real time monitoring and notification via the Wi-Safe Connect platform of domestic alarm installations.

Diameter 125mm

Depth 31mm

Weight 191g



Product Features

- The WG-1 gateway allows for all devices utilising Wi-Safe 2 wireless communication to connect to the internet. The diagnostic information held within an individual WS2 device is sent directly to a personalised cloud based dashboard, where alerts can be managed and responses initiated.
- For use with Fireangel devices based on the Wi-Safe 2 wireless technology.
- Connect to the Internet via an Ethernet cable Hub.
- 3 LEDs to indicate Power, Fault, and Communication.
- Power supply via enclosed power unit.
- For further information visit www.wi-safeconnect.com

Technical Specification

Power	230V Mains Powered, 5V DC, 1.5A.
Technology	Wi-Safe 2
Internet connection	RJ45 lead (Ethernet)
Installation positions	Free-standing / Wall
Warranty	2 years
Master pack quantity	4
Max No. of connected devices	50 units
Networking	Multi-directional communication
Compatibility	Compatible with all products with Wi-Safe 2, including use in mixed systems (i.e of mains and battery powered products).
Independently tested to	EN 301 220-2 V 2.4.1 EN 301 489-3 V 1.6.1 EN 301 489-1 V 1.9.2
Range	35m (over 200m in clear air)

